

UniFi UISP Branding

Q

Search UniFi products

Switching WiFi Camera Security Door Access Integrations Advanced Hosting

PTZ > [G5 PTZ](#)

Datasheet

In The Box

Marketing Images

Installation Guide



Overview

	Without mount: Ø90 x 152.5 mm (Ø3.5 x 6")
Dimensions	With mount: 90 x 94 x 179.5 mm (3.5 x 3.7 x 7")
IR Night Vision	20 m (65 ft)
Optical Zoom	2K
Smart Detections (People, Vehicles, Animals)	✓
Resolution	2K
Field of View	Wide: H: 99.7°, V: 51.9°, D: 121° Tele: H: 45.5°, V: 25.4°, D: 52.4°
Audio	Microphone
Weatherproofing	IP66
Tamper Resistance	IK04
Mounting	Wall mount, pole mount (Included) Conduit adapter, surface, in-ceiling, pendant, corner mount (Optional)

^ Performance

Networking Interface 10/100 MbE RJ45 port

Video

Max. Frame Rate 30 FPS

Resolution 4MP 2688 x 1512 (16:9)

Optics

Sensor 5MP 1/2.7" CMOS

Lens F 3.42–6.85 mm; f/1.85–f/2.4

Night Mode Built-in IR & white LED illumination with IR cut filter

^ Hardware

Max. Power Consumption 14W

Supported Voltage Range 37—57V DC

Power Method PoE+

Pole Mount Diameter 1.5–2" (38–50 mm)

Weight Without mount: 580 g (1.3 lb)
With mount: 650 g (1.4 lb)

Enclosure Material Aluminum alloy, polycarbonate

Mount Material Wall mount: polycarbonate
Pole mount: aluminum alloy

Button (1) Factory-reset

Ambient Operating Temperature -30 to 45° C (-22 to 113° F)

Ambient Operating Humidity 0 to 90% noncondensing

Certifications CE, FCC, IC

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2025 Ubiquiti, Inc. All rights reserved.