

UniFi UISP Branding

Q

USW-WAN-EU

- Switching
- WiFi
- Camera Security
- Door Access
- Integrations
- Advanced Hosting



WAN > [WAN Switch](#)

Datasheet

In The Box

Marketing Images

Installation Guide



Overview

Dimensions

442.4 x 120 x 43.7 mm
(17.4 x 4.72 x 1.7")

Port Layout

1 GbE RJ45	1 (1G/100M/10M)
10G SFP+	3 (10G/1G)
Redundancy	(2) AC inputs
Form Factor	Rack mount (1U)

Performance

Switching Capacity	20 Gbps
Total Non-Blocking Throughput	10 Gbps
Forwarding Rate	15 Mpps

Hardware

Max. Power Consumption	13W
Power Method	(2) Universal input, 100—240V AC, 50/60 Hz
Power Input Method	AC input
Power Supply	(2) AC/DC, internal, 36W
Supported Voltage Range	100—240V AC
Management	Ethernet
Weight	Without mounting brackets: 2.2 kg (4.85 lb) With mounting brackets: 2.3 kg (5.1 lb)
Enclosure Material	SGCC steel
Mount Material	SGCC steel
ESD/EMP Protection	Air: $\pm 16\text{kV}$, contact: $\pm 22\text{kV}$
Ambient Operating Temperature	-5 to 40° C (23 to 104° F)
Ambient Operating Humidity	10 to 90% noncondensing
LEDs	
Ethernet	✓
SFP+	✓
System	✓
Certifications	CE, FCC, IC
NDAA Compliant	✓

^ Software

Application Requirements

UniFi Network	Version 9.1.119 and later
---------------	---------------------------

Stay in Touch

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2025 Ubiquiti, Inc. All rights reserved.