

WiFi Switching Cloud Keys & Gateways Camera Security Door Access Power Tech New I


Switching > [Flex Mini](#)

Datasheet

In The Box

Marketing Images

Installation Guide



Mechanical

Dimensions	107 x 70 x 21 mm (4.2 x 2.8 x 0.8")
Weight	150 g (5.3 oz)
Enclosure material	Polycarbonate

Hardware

Management interface	Ethernet In-Band
Networking interface	(5) GbE RJ45 ports

Total non-blocking throughput	5 Gbps
Switching capacity	10 Gbps
Forwarding rate	7.44 Mpps
Power method	(1) USB Type C, 5V (1) PoE/PoE+, 44—57V DC, 0.05—0.04A
Power supply	5V, 1A power adapter* *Only single-unit packages include the 5V, 1A USB-C power adapter.
Supported voltage range	USB Type C: 4.7—5.3V DC PoE/PoE+: 44—57V DC
Max. power consumption	2.5W
ESD/EMP protection	Air: ± 16kV, contact: ± 12kV
Button	Factory reset
Ambient operating temperature	-5 to 45° C (23 to 113° F)
Ambient operating humidity	10 to 90% noncondensing
Certifications	CE, FCC, IC

Switching Features

Layer 2 features	Port isolation Storm control Port mirroring Multicast / broadcast rate limiting Flow control Jumbo frames Egress rate limit
Layer 3 features	-

LEDs

System	Status
Ethernet	Speed/link/activity

Application Requirements

Stay in Touch

Email

Subscribe



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.