



[WiFi](#)
[Switching](#)
[Cloud Keys & Gateways](#)
[Camera Security](#)
[Door Access](#)
[Managed VoIP](#)
[New](#)

Accessories > [LTE Backup Pro](#)

[Datasheet](#)

[Marketing Images](#)

[Installation Guide](#)



Mechanical

Dimensions 66 x 202 x 32 mm (2.6 x 8 x 1.3")

Weight
 Without stand: 223 g (7.9 oz)
 With stand: 336 g (11.9 oz)

Enclosure material Polycarbonate

Mount material
 Stand: aluminium
 Wall mount: polycarbonate

Hardware

Processor	74 Kc MIPS processor at 775 MHz
Memory	128 MB DDR2
Networking interface	(2) GbE RJ45 ports LTE Category 4 radio
Management interface	Ethernet
PoE interface	(1) PoE in (PoE output not used) (1) PoE passthrough output (Requires a PoE+ switch)
SIM	nano-SIM* *Data-only.
LTE bands	Band 2, 4, 5, 12, 14, 66
Operator	AT&T network* US only.
Power supply	UniFi PoE switch 48V, 0.5A PoE adapter
Supported voltage range	44—57V DC
Max. power consumption	Excluding PoE passthrough output: 8.5W
Max. PoE passthrough wattage per port	15.4W* *Requires a PoE+ switch
MIMO	2 x 2 LTE Category 4
Throughput speeds*	Download 150 Mbps / Upload 50 Mbps * Speed and coverage depend on location and network performance.
Antenna	(2) Internal LTE antennas (1) Female RP-SMA connector for an external antenna (optional)* *The maximum antenna gain must not exceed 6 dBi to comply with regulation.
External antenna port*	Female RP-SMA connector *Please use male RP-SMA antennas to match the U LTE Backup Pro.
LCM display	1.54" screen
Button	Factory reset
Mounting	Wall mount or foot stand (Included)
Ambient operating temperature	-10 to 60° C (-14 to 140° F)
Ambient operating humidity	5 to 95% noncondensing

Certifications

FCC, IC

Software

Management application

UniFi Network: Version 7.2.85 and later

Stay in Touch



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.