UniFi   UISP   Branding

🔍 Search UniFi products

| Switching | WiFi | Camera Security | Door Access | Integrations | Advanced Hosting |

Dome & Turret > G6 Turret

| Datasheet | In The Box | Marketing Images | Installation Guide |

⌃ Overview

Dimensions	Ø100 x 95 mm (Ø3.9 x 3.7")
IR Night Vision	30 m (98 ft)
Face Recognition	✓
License Plate Recognition	✓
Smart Detections (People, Vehicles, Animals)	✓
Resolution	4K
Field of View	H: 109.9°, V: 56.7°, D: 134.1°
Audio	Microphone

box (Optional)

Networking Interface	10/100 MbE RJ45 port

Video

Image Settings	Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay, HDR
Max. Frame Rate	30 FPS
Resolution	8MP 3864 x 2160 (16:9)

Optics

Sensor	1/1.8" 8MP
Lens	Fixed focal length
Night Mode	Built-in IR LED illumination and IR cut filter

⌃ Hardware

Max. Power Consumption	12.5W
Supported Voltage Range	37–57V DC
Power Method	PoE
Processor	Quad-core Arm® Cortex®-A53 based chip
Weight	550 g (1.2 lb)
Enclosure Material	Aluminum alloy, polycarbonate
Button	(1) Factory-reset
Ambient Operating Temperature	-30 to 50° C (-22 to 122° F)
Ambient Operating Humidity	0 to 90% noncondensing
Certifications	CE, FCC, IC
NDAA Compliant	✓

Cable

Cable Connector Type	RJ45

...ner

...2.8")

Jacket Enclosure Material   Thermoplastic elastomer, polycarbonate, silicone rubber

Stay in Touch

Email

Subscribe

Terms of Service | Privacy Policy | Legal | Cookies Settings

© 2025 Ubiquiti, Inc. All rights reserved.

By clicking "Accept All Cookies", you agree to the storing of cookies on your device to enhance site navigation, analyze site usage, and assist in our marketing efforts.