

60 GHz Wireless

Wireless

Fiber


Wired

Accessory Tech

Wireless > [airMAX LiteBeam 5AC](#)

Datasheet

Marketing Images



*Compatible with airMAX ac devices.
 **24V DC, 0.3A GbE PoE adapter included.

Mechanical

Dimensions 358 x 271.95 x 272.5 mm (14.1 x 10.7 x 10.7")

Weight Without mount: 800 g (1.8 lb)
 With mount 980 g (2.2 lb)

Wind survivability 200 km/h (125 mph)

Wind loading 275 N at 200 km/h (61.8 lbf at 125 mph)

Hardware

Networking interface	(1) GbE RJ45 port
Power method	Passive PoE 2-pair (4, 5+; 7, 8 return)
Power supply	24V, 0.3A gigabit PoE adapter (Included)
Supported voltage range	22-27V DC
Max. power consumption	7W
Max. power output	25 dBm
Gain	23 dBi
Ambient operating temperature	-40 to 70° C (-40 to 158° F)
Ambient operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

Operating Frequency (MHz)

Worldwide	5150-5875 MHz
USA	
U-NII-1	5150-5250 MHz
U-NII-2A	5250-5350 MHz
U-NII-2C	5240-5725 MHz
U-NII-3	5725-5850 MHz

Management Radio (MHz)

Worldwide	2412 - 2472 MHz
US/CA	2412 - 2462 MHz

[Compliance Information](#)

Stay in Touch



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.