



ALLNET

ALL2295v2

IP-Cam Megapixel Outdoor Fix-Dome FULL HD

- *Progressive Scan CMOS Sensor*
- *Full HD 1080p / HD 720p Real-Time Dual Streaming*
- *H.264 and MJPEG Kompression*
- *Remote Zoom & Focus (Motorized Lens)*
- *Motion Detection*
- *Privacy Masks*
- *Tag/Nacht Modus (23x integrierte IR-LED)*
- *Micro SD Support*
- *Kabel Management*
- *Wetterfest / Outdoor geeignet (IP66 international)*
- *ONVIF Support*

Art. Nr. 92886



Item		
Camera		
Image Sensor		1/2.7" Progressive Scan CMOS
Effective Pixels		1920(H) x 1080(V)
Minimum Illumination	Color	0.2 lux
	B/W	0.02 lux
Shutter Speed		1 - 1/10000 sec.
White Balance		Manual / AWB / ATW
Lens		
Lens Type	Vari-focal/Motorized	F1.2 / f = 3-9 mm
FOV (16:9 resolution)		103.5° (W) - 34.3° (T)
Operation		
Video Compression		H.264/MJPEG
Video Streaming		Simultaneous H.264 1080p (25/30 fps) + MJPEG D1 (25/30 fps)
		Simultaneous H.264 1080p (25/30 fps) + H.264 D1 (25/30 fps)
Resolution	H.264	Full HD 1080p/SXGA/HD 720p/XGA/SVGA/D1/VGA/CIF
	MJPEG	Full HD 1080p/SXGA/HD 720p/XGA/SVGA/D1/VGA/CIF
Image Setting	Brightness	Manual
	Exposure	Auto / Manual
	Sharpness	Manual
	Contrast	Manual
	White Balance	Auto / Manual
	Saturation	Manual
	Hue	Manual
	Backlight Compensation	On/Off
	Digital Zoom	Support
	WDR	On/Off
	3D Noise Reduction	On/Off
	Motion detection	On/Off
	Privacy Mask	On/Off
	Privacy Mask Type	Color
	ICR*	Auto/On/Off
Audio	Tampering Alarm	On/Off
	Two-way Audio	Line out, Line in/mic in
Alarm	Compression	G.711/G.726
	Input	5V 10kΩ pull up
Event Notification	Output	Photo Relay Output 300VDC/AC
	Multiple Languages	HTTP, FTP, SMTP
Network		English, French, German, Italian, Korean, Simplified Chinese, Traditional Chinese, Russian
Interface		10/100Mbps Ethernet (RJ-45)
Protocol		IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF
Password Levels		User and Administrator
Security		HTTPS, IP Filter, IEEE 802.1X
Internet Browser		Internet Explorer (6.0+), Chrome, Firefox, Safari
User Account		20
Mechanical		
Built-in IR Illuminator*	Working distance	up to 25m
	Wavelength	850nm
	Number of LEDs	24
Connectors	Power	3 pins terminal block
	Ethernet	RJ-45
	Micro SD	microSDHC 32GB support
	Audio	4 pins terminal block
	Alarm In/Out	4 pins terminal block
	Analog Video	1.0 Vp-p / 75 Ω, BNC
LED Indicator		Power, Link, ACT
General		
Operating Temperature		35° C - 50° C (14° - 122° F) powered by DC12V: -30° C - 50° C (-22° - 122° F) powered by AC24V: -35° C - 50° C (-31° - 122° F) Humidity: 10% to 90%, no condensation integrated heater and motorized Varifocal 3-9mm
Power Source		DC12V/AC24V/PoE
Power Consumption		System: 5W (Heater: +6W, Fan: +1W, Built-in IR Illuminator: +3W, Motorized Lens: +3.6W)
Weatherproof Standard		IP66
Regulatory		CE, FCC, RoHS Compliant
Dimension	Indoor*	ø 151 x 130 mm (ø 5.9 x 5.1 inches)
	Outdoor	
Weight	Indoor*	0.8 kg (1.8 lbs)
	Outdoor	

* mark for optional items